



2

Number
of
stages

CO₂

Carbon
Dioxide

6.725

Design Flow
Capacity
[kg/hr]

433

Absorbed
power
[kW]

1,17 - 19,8

Suction/Discharge
Pressure
[Bar A]

2.950

Speed
[rpm]

C

Series

The Compound CO₂ units is installed a purification facility to deliver a supply of high quality carbon dioxide (CO₂).

The package has been designed in Mayekawa Europe and assembled in its workshop according to the PED rules.

Compressor	2520LS-LBL
Capacity	6.725 kg/hr + 100 kg/hr side load
Gas Handled	Carbon Dioxide
Working conditions	1,7 - 19,8 Bar A
EM installed	500 kW 400V/3Ph/50Hz
Codes:	JIS – ASME B31.5
Installation:	Indoor - Non Hazardous Area
Final Destination:	Slovakia
Delivery	09/2022



Special Configurations

- Local JB.
- Electrical motor suitable for D.O.L.
- Fixed speed
- Footprint LxWxH 4.655 x 2.370 x 3.600 mm
- Weight 22.000 kg

LCH 2022-06



Mayekawa Italia s.r.l.

HQ: Via Riccardo Lombardi 19/12 - 20153 Milano - Italia
Ph: +39 02 4892 9218 - Fax: +39 02 4531 728

OO: Via Pradazzo, 7 - 40012 Calderara di Reno - Bologna - Italia
Ph: +39 051 726 364 - Fax: +39 051 726 804

E-mail: standard-package@mayekawa.it - Website <https://mayekawa.it/>

